

## Galaxy™ & Ultronic™ Technical Specifications

### Technical Data



Galaxy™: Certified to ANSI/UL Std. 499 Conforms to CAN/CSA Std. 22.2 No. 36  
 Ultronic™: Certified to ANSI/UL Std. 50 Conforms to CAN/CSA C22.2 No. 113

ISO 9001  
 CERTIFIED

Hand Dryer Model	Galaxy™ 1	Galaxy™ M 1	Galaxy™ 2	Galaxy™ M 2	Ultronic™ -1 Plus	Ultronic™ -1 Premium	Ultronic™ -2 Plus	Ultronic™ -2 Premium
Item number	073009	073724	073010	073725	205634	205636	205635	205637
<b>ELECTRICAL DATA</b>								
Phase - 60/50 Hz	single	single	single	single	single	single	single	single
Voltage	120 v	120 v	240 v or 208 v	240 v or 208 v	120 v	120 v	240 v or 208 v	240 v or 208 v
Wattage	1850 w	1850 w	2000 w   1500 w	2000 w   1500 w	820 w	820 w	750 w   640 w	750 w   640 w
Amperage	15.42 A	15.42 A	8.34 A   7.21 A	8.34 A   7.21 A	6.8 A	6.8 A	3.5 A   3.5 A	3.5 A   3.5 A
Required circuit breaker size <sup>1</sup>	20 A	20 A	15 A	15 A	15 A	15 A	15 A	15 A
Required wire size <sup>2</sup>	12 AWG	12 AWG	12 AWG	12 AWG	16 AWG	16 AWG	18 AWG	18 AWG
<b>DIMENSIONS</b>								
Height	9 7/8" (250 mm)	10 1/2" (266 mm)	9 7/8" (250 mm)	10 1/2" (266 mm)	12 3/16" (309 mm)	12 3/16" (309 mm)	12 3/16" (309 mm)	12 3/16" (309 mm)
Width	9 1/16" (230 mm)	9 1/8" (232 mm)	9 1/16" (230 mm)	9 1/8" (232 mm)	10 11/16" (272 mm)	10 11/16" (272 mm)	10 11/16" (272 mm)	10 11/16" (272 mm)
Depth	9 1/16" (230 mm)	9 1/16" (230 mm)	9 1/16" (230 mm)	9 1/16" (230 mm)	5 3/16" (132 mm)	5 3/16" (132 mm)	5 3/16" (132 mm)	5 3/16" (132 mm)
<b>WEIGHT</b>								
Weight	5.5 lb (2.5 kg)	8.8 lb (4.0 kg)	5.5 lb (2.5 kg)	8.8 lb (4.0 kg)	6.2 lb (2.8 kg)	8.8 lb (4.0 kg)	6.2 lb (2.8 kg)	8.8 lb (4.0 kg)
<b>CONSTRUCTION</b>								
Color	Alpine White	Alpine White Optional: Charcoal Gray Silver Metallic	Alpine White	Alpine White Optional: Charcoal Gray Silver Metallic	Alpine White	Stainless Steel	Alpine White	Stainless Steel
Housing	ABS polycarbonate	Cast aluminum	ABS polycarbonate	Cast aluminum	Polycarbonate	Stainless Steel	Polycarbonate	Stainless Steel
Degree of protection (IP)	IP 23	IP 23	IP 23	IP 23	IP X3	IP X3	IP X3	IP X3
<b>OTHER</b>								
Sound level	53 dB(a)	53 dB(a)	53 dB(a)	53 dB(a)	76 dB(a)	76 dB(a)	76 dB(a)	76 dB(a)
Air speed	NA	NA	NA	NA	215 mph (96 m/s)	215 mph (96 m/s)	215 mph (96 m/s)	215 mph (96 m/s)
Air volume	90.0 CFM	90.0 CFM	95.0 CFM	95.0 CFM	49.5 CFM	49.5 CFM	49.5 CFM	49.5 CFM
Drying time	30 seconds	30 seconds	30 seconds	30 seconds	10-12 seconds	10-12 seconds	10-12 seconds	10-12 seconds

<sup>1</sup> This is our recommendation as the manufacturer. Check local codes for compliance if necessary. <sup>2</sup> Copper must be used